

IN THE CLAIMS

1 Claim 1 (original) A portable enclosure apparatus, comprising:

5 a frame assembly having a bottom wall with a peripheral edge portion, an upper frame member, and first and second support members with opposite end portions operatively coupled with said bottom wall and said upper frame member; said first and second support members being positioned to extend outwardly from said bottom wall from a common axis that extends through said bottom wall proximal a long or a short axis of said bottom wall; and

10 enclosure means operatively coupled with said bottom wall and said upper frame member for generally forming a chamber extending between said bottom wall and said upper frame member.

15 Claim 2 (original) The apparatus of claim 1 wherein said first and second support members have a length that is selectively adjustable between extended and retracted positions.

 Claim 3 (original) The apparatus of claim 2 wherein said first and second support members are comprised of first and second portions that are selectively telescopically movable with respect to one another.

20 Claim 4 (original) The apparatus of claim 3 wherein the first portions of said first and second support members are provided with gripping means for selective manipulation by a user to telescopically set a desired length for said first and second support members.

1 Claim 5 (original) The apparatus of claim 4 wherein the second portions of said first and second support members are provided with receiving means for at least partially receiving said gripping means when said first and second support members are adjusted between said extended and retracted positions.

5 Claim 6 (original) The apparatus of claim 1 wherein said bottom wall is comprised of a bottom frame member and a bottom platform.

Claim 7 (currently amended) The apparatus of claim 6 wherein said upper frame member and said bottom platform are of similar dimensions.

10 Claim 8 (original) The apparatus of claim 7 wherein said bottom wall is selectively removably coupled with said first and second support members and said first and second support members are removably coupled with said upper frame so that said frame assembly may be selectively collapsed for storage or transport.

15 Claim 9 (original) The apparatus of claim 8 wherein said bottom frame member and said bottom platform are removably coupled with one another.

Claim 10 (original) The apparatus of claim 9 further comprising a plurality of casters coupled to said bottom wall so that said frame assembly may be selectively positioned along an operating surface.

20 Claim 11 (currently amended) The apparatus of claim 10 wherein said casters are removably ~~remarkably~~ coupled with said bottom wall.

25 Claim 12 (original) The apparatus of claim 2 wherein said bottom wall is selectively removably coupled with said first and second support members and said first

1 and second support members are removably coupled with said upper frame so that said
frame assembly may be selectively collapsed for storage or transport.

5 Claim 13 (original) The apparatus of claim 12 wherein the first portions of said
first and second support members are provided with gripping means for selective
manipulation by a user to telescopically set a desired length for said first and second
support members.

10 Claim 14 (original) The apparatus of claim 13 further comprising a plurality of
casters coupled to said bottom wall so that said frame assembly may be selectively
positioned along an operating surface.

15 Claim 15 (original) The apparatus of claim 1 wherein said bottom wall has a
forward edge portion and a rearward edge portion and said first support member
extends outwardly from a point proximal the center of said forward edge portion and
said second support member extends outwardly from a point proximal the center of said
rearward edge portion.

Claim 16 (original) The apparatus of claim 15 wherein said first and second
support members have a length that is selectively adjustable between extended and
retracted positions.

20 Claim 17 (original) The apparatus of claim 16 wherein said bottom wall is
selectively removably coupled with said first and second support members and said first
and second support members are removably coupled with said upper frame so that said
frame assembly may be selectively collapsed for storage or transport.

1 Claim 18 (original) The apparatus of claim 17 wherein the first portions of said
first and second support members are provided with gripping means for selective
manipulation by a user to telescopically set a desired length for said first and second
support members.

5 Claim 19 (original) The apparatus of claim 18 wherein the second portions of said
first and second support members are provided with receiving means for at least
partially receiving said gripping means when said first and second support members are
adjusted between said extended and retracted positions.

10 Claim 20 (original) The apparatus of claim 19 further comprising a plurality of
casters coupled to said bottom wall so that said frame assembly may be selectively
positioned along an operating surface.